





## Electronic Scale

### FEATURES:

- Powered by 6 “D” batteries or 9V adapter
- Long battery life
- Super contrast display provides superior readability under the bright sunshine or even under dim light
- Small size yet sturdy construction makes the scale extremely portable
- Preset keys allow you to recall the unit price by one touch and eliminate errors
- Fast weighing speed



**5950685** DS685B 30-lb. battery-operated scale with 14 preset keys, with auto power-off, no post display

## Electronic Printer

### FEATURES:

- “Touch” screen for simple operation
- Up to 576 preset keys on the screen
- Supports labels from 20mm to 60mm wide and 20mm to 240mm long
- 16 standard formats and 8 custom formats
- Small size yet sturdy construction makes the scale extremely portable
- Memory size 1 meg std, up to 8 meg optional
- Operating temperature 14°F to 104°F
- Operating humidity 85% RH maximum
- Standard Interfaces: IBM keyboard, RS-232, and either RS-422 or Ethernet
- Supports labels from 20mm to 60mm wide and 20mm to 240mm long

**Excellent  
Bakery  
Printer**



- 5101375** DP90 multi-purpose printer with 1 meg memory, 110V, 60 Hz, 1-phase, 9” x 14” x 12”, with Ethernet board
- 3351330** 40mm x 28mm DP-90 / DP-120 blank white label, 2000 labels per roll, outside wind



## Digital Scales

The SM-90 series offers wide model variations to suit numerous sales counter applications



Advanced Network System for Information Technology



### SPECIFICATIONS



**SM90-N  
NUMERIC DISPLAY**



**SM90-EP  
ALPHA-NUMERIC DISPLAY**

**Ethernet /  
Wireless Capable**

### Supports Wired or Wireless communication configurations:

- PC Host to Standalone Scale
- PC Host to Master scale with Slave Scales
- Single or Multiple Standalone Scale
- PC Host to Multiple Standalone Scales
- Master Scale and Multiple Slave Scales

<b>Capacity :</b>	30 lb.
<b>Dual Range:</b>	1-15 lbs. x 0.005 lb. 15-30 lbs. x 0.01lb.
<b>Display:</b>	Fluorescent Display SM-90N - Numeric SM-90EB - Sequential Alpha-Numeric SM-90EP - Sequential Alpha-Numeric
<b>Power Source:</b>	AC 110V, 60 Hz, 30 W, .3 Amps
<b>Electrical Approval:</b>	CSA
<b>Operating Temp:</b>	14 to 104 F
<b>Operating Humidity:</b>	85 (%RH) at max.
<b>Keys:</b>	32 presets, 15 functions (SM-90N/EB) 56 presets, 15 functions (SM-90EP)
<b>Label Size:</b>	Max. 60mm(W) x 240mm(L)
<b>Label Formats:</b>	Built-in formats for common label sizes as well as custom programmable formats
<b>Printer:</b>	60mm wide, 190 DPI High Speed Direct Thermal Imaging
<b>Printer Characters:</b>	Standard Alphabet and other characters
<b>Memory Size:</b>	1MB standard (approx. 3,000 PLU) <b>Optional up to 6MB</b> (approx. 7,000 - 23,000 PLU)
<b>Standard Interface:</b>	FL-1 (RS-232C), IBM Keyboard, Ethernet (10 Base-T), RS-485
<b>Dimensions:</b>	15W x 16.4D x 6.2H inches (SM-90N/EB) 15W x 18D x 20.5H inches (SM-90EP)

**5953730** SM-90N scale/prINTER with 1 meg memory, numeric display, no post, no Ethernet interface)

**5953425** SM-90EN scale/prINTER with 1 meg memory, numeric display, no post

**5953715** SM-90EB scale/prINTER with 1 meg memory, alpha-numeric display, no post

**5953815** SM-90EP scale/prINTER with 1 meg memory, alpha-numeric display, with post

**6000099** Wireless communication card for SM-90 scales, HSB card

Signal Hill, CA.  
(562) 595-4785

2667 Gundry Avenue, 90755 • (Corporate)

OFFICE  
ADDRESSES

[www.pbimarketing.com](http://www.pbimarketing.com)

Tracy, CA.  
(209) 839-9280

252 Larch Road Suite A, 95304



## Digital Scales

### SM-780 Series

A PC Based Scale powered by the Linux Operating System offers flexible/custom capabilities. Enhanced features promotes a variety of diverse networking, training & merchandising options!



#### SPECIFICATIONS



Capacity :	30 lb. x 0.01
Display:	Large Color STN LCD Operator: SVGA Touch Panel Customer: VGA Color Panel Tare Weight: 4 Digits Weight: 5 Digits Unit Price: 11 Digits Total Price: 9 Digits
Power Source:	AC 110V, 60 Hz, 30 W, .3 Amps
Electrical Approval:	CSA
Operating Temp:	14 to 104 F
Operating Humidity:	85 (%RH) at max.
Keys:	Custom Bitmap Key Layouts
Label Size:	Max. 80mm (W) x 240mm (L)
Label Formats:	Built-in formats for common label sizes as well as custom programmable formats
Printer:	80 mm wide, 190 DPI High Speed Direct Thermal Imaging
Printer Characters:	Standard Alphabet and other characters
Standard Interface:	Asynchronized Serial Com1, Com2 Ethernet USB Ports Standard PS2 Keyboard/Cash Drawer
Memory Size:	DIMM Socket Support 16MB to 256MB
Dimensions:	23W x 16D x 6H

- Attractive, interactive displays
- Audio visual clips for advertisements, promotions or cooking demonstrations enhance your marketing and customer service capabilities
- Open architecture and easy integration with existing systems/backroom operations
- Improved performance, with easy operation and training
- Self-diagnostic capabilities
- Easy customization and diverse applications

**5950780** SM-780  
**6000900** Seafood platter



**Automatic Wrapper** **AW3600 Series**



**The Integrated Fully Automatic Weigh / Wrap / Label System**

**The AW-3600 series changes the packaging operation of your backroom with Dynamic Film Stretching**

- Wrap a wide range of packages with just one film size
- Wrapping speed of up to 30 packages per minute with one operator
- Automatic tray size detection for simple and speedy operation
- Automatic label application with robot arm for flexible and accurate labeling
- Easy and fast film loading from front of machine



**HUGE Film Savings!**

**One 16" Film Roll Wraps All Tray Sizes**

**Small Footprint Uses Less Floor space**

**SPECIFICATIONS**

<b>Package Size:</b>	Width: 130mm - 380mm (5.1" - 15") Height: 10mm - 130mm (0.4" - 5.1") Depth: 80mm - 254mm (3.1" - 10")	<b>Printing Device:</b>	Thermal head with history control
<b>Wrapping Speed:</b>	Max. 30 packages/min.	<b>Usable Label:</b>	Thermal paper (width = 60mm/75*mm) * factory option
<b>Number of Film Rolls:</b>	1	<b>Label Size:</b>	12 sizes available
<b>Weighing:</b>	Single Interval type Capacity: Max. 30 lb. Scale Interval: e = 0.01 lb. Weighing Range: 0.20 lb. - 30 lb. Max. Wrapping Capacity: 11 lb.	<b>Display Panel:</b>	LCD with photo-sensors (touch screen)
<b>Labeler Type:</b>	Up to 4 labelers	<b>Externals:</b>	Stainless steel construction
		<b>Power Supply:</b>	3-phase, 208V, 50/60 Hz
		<b>Net weight:</b>	480 kg
		<b>Operating Temp:</b>	32° F - 95° F
		<b>Operating Humidity:</b>	90% RH (max.)

- 8052005** AW3601 super stretch automatic wrapper with 1 meg memory, 220V, 3-phase, uses one roll of 16" film, no compressor required
- 6000645** 30" conveyor only for galvanized label cabinet
- 2350016** 16" film for super stretch wrapper per 5000'-ft. roll, 62 gauge
- N05303** Commodity holder with swivel base and 2" ring capacity
- 6000095** Galvanized label cabinet with poly top & 30" roller conveyor
- 6000608** S/S meat tray stand for back room wrapper system
- 6007475** Scalemate wrap station with adj. shelf, platform, two side wings, 2-roll wrapper, 6" x 15" hot plate (UL)

Signal Hill, CA.  
(562) 595-4785  
2667 Gundry Avenue, 90755 • (Corporate)

OFFICE  
ADDRESSES  
www.pbimarketing.com

Tracy, CA.  
(209) 839-9280  
252 Larch Road Suite A, 95304



## AW 4600

The new & improved integrated fully automatic weigh/wrap/label system.

### The AW-4600 combines high speed and DIGI's proven Super-Stretch Technology for a superior backroom operation!

\* Advanced Fiber Optic sensor technology with larger infeed - improved automatic tray size detection, including clear, black and oversize trays.

\* Large Full Color Touch Screen Display with customer specific layout, PLU Searching, and easy operation.

\* High Productivity, weighs/wraps and labels up to 36 packs per minute with unparalleled finish.

\* DIGI's exclusive Rotbot Arm applicator for accurate label placement everytime!

\* Fast and Easy Film change from front of machine made famous by the AW-3600 is still the best in the business.

\* Wrap a wide range of packages with one roll of film!



One 16" Film Roll Wraps All Sizes

Compact Design with all operations carried out from front of machine uses less floor space!

#### SPECIFICATIONS

Package Size:	Width: 130mm - 380mm (5.1"-15") Height: 10mm - 150mm (0.4"-5.9") Depth: 80mm - 254mm (3.1"-10")	Printing Device:	Thermal head with history control
Wrapping Speed:	Max. 36 packages/minute	Usable Label:	Thermal paper (up to 80mm wide)
Number of Film Rolls:	1	Display Panel:	10.4" TFT Color
Weighing:	<i>Single Interval type</i> Capacity: Max 30Lb x 0.01 Max. Wrapping Capacity: 11Lb	Externals:	Stainless Steel Construction
Labeler Type:	Up to 4 Labelers	Power Supply:	3-phase, 208V, 50/60 Hz
		Net Weight:	480 Kg
		Operating Temp:	32° F - 95° F
		Operating Humidity:	90% RH (max.)

\*The AW-4600 Multi-Labeling System (fully integrated POP and Bottom Labellers) performs all labeling in one process!

- 8054600** AW 4600
- 6000645** 30" conveyor only for galvanized label cabinet
- 2350016** 16" film for super stretch wrapper per 5000'-ft. roll, 62 gauge
- N05303** Commodity holder with swivel base and 2" ring capacity
- 6000095** Galvanized label cabinet with poly top & 30" roller conveyor
- 6000608** S/S meat tray stand for back room wrapper system
- 6007475** Scalemate wrap station with adj. shelf, platform, two side wings, 2-roll wrapper, 6" x 15" hot plate (UL)