

SM-5500 PC Based Scale



SM-5500 BCON 5955500

DIGI SM-5500 is a PC Based scale that will boost operations revenue, enhance operations with integrated queue and collection system through various innovative functions.

Linerless Labels with Auto-Cutter Available

The SM-5500 is available with an optional built-in auto-cutter feature for linerless labels. The system can automatically detect label size, so only one type of label is required for all printed labels.

Interactive Screen Display

SM-5500 is available in 12" WVGA customer display screen that can display customized information, such as recipes, promotions, and advertisements. The screen has the ability to show both video and still images on customer display.

SM-5300 PC Based Scale



5955300

DIGI SM-5300 is a PC Based weigh-labeler offering linerless function with the auto-cutter feature.

Economical, Efficient, & Eco-Friendly

Without the liner film sheet, the number of labels per roll will be increased significantly. Operational period is lengthened with few pauses for label changing downtime.

Interactive Customer Display

SM-5300 comes with a 7" WVGA customer display that shows useful information to your customer, such as recipes, up sell, and cross sell. The screen has the ability to show still images on customer display.

SM-6000 PC Based Scale



5956000

DIGI SM-6000 is equipped with an innovative 8" high contrast color customer display and three groundbreaking technologies that free up time and space for user: Built in wireless, integrated Speed ID and info tag support included.

Functional and Intuitive Interface

A new user interface with multi-gesture provides a natural and intuitive operation. Even first-time users with little or no training are able to operate system.

Linerless Label Functionality with Auto-Cutter

Fit in twice as many label prints on a single label roll without the liner film sheet and enjoy zero backing paper waste at work. Create different label prints of variable lengths at ease and reduce roll replacement for workplace efficiency.

Speed ID: Clerks wear a Speed ID tag on their uniform, which is detected automatically by standing in front of the scale.

MORE INFO ON NEXT PAGE →



General 5955500

Power Source :	AC 100/110 or 220/230/240 Volts (50/60 Hz) Auto Switch
Dimensions : mm/in	385/15.16 (W) X 446/17.55 (D) X 148/5.83 (H)
Net weight :	Approx. 12.0 kg
Operation humidity :	15% to 85% RH

Consoles

Operator Display and Customer Display :	7" WVGA with Touch Panel (800 x 480 mm), Adjustable Display 12" TFT with Touch (800 x 600 mm)
Memory :	8 GB SD Std, Upgradeable to 128 GB
Standard Interface :	Ethernet 10/100 Base T, USB 2.0 Host
Number of Preset Keys :	Up to 16,000 Touch Screen Preset Keys, 28 Mechanical Keys

Printer

Print Method :	Direct Thermal Printing
Print Resolution :	300 dpi
Printing Width :	30-80 mm (1.18-3.15 in)
Printing Length :	28-240 mm (1.10-9.45 in)
Print Speed :	Up to 150 mm/sec
Label Roll Diameter:	Outer- 4.92 in / Interior- 1.63 in

Weighing

Capacity :	Max. 30 lb
Single-Range :	0-30 lb x 0.01 lb
Dual-Range :	0-15 lb x 0.005 lb

General 5955300

Power Source :	AC 100/110 or 220/230/240 Volts (50/60 Hz)
Dimensions : mm/inches	360/14.17 (W) X 472/18.58 (H) X
Net weight :	Approx. 10.5 kg
Operation humidity :	15%-85% RH Non-Condensation

Consoles

Operator Display and Customer Display :	7 in WVGA with Touch Panel (800 x 480 mm) Adjustable Display
Memory :	8 GB SD Std, Upgradable to 128 GB
Standard Interface :	Ethernet 10/100 Base T, USB 2.0 Host
Number of Preset Keys :	Up to 16,000 Touch Screen Preset Keys, 28 Mechanical Keys

Printer

Print Method :	Direct Thermal Printing
Print Resolution :	200 dpi
Printing Width :	40-56 mm (1.57-2.20 in)
Printing Length :	28-240 mm (1.10-9.45 in)
Print Speed :	Up to 120 mm/sec
Label Roll Diameter:	Outer- 4.92 in / Interior- 1.63 in

Weighing

Capacity :	Max. 30 lb
Single-Range :	0-30 lb x 0.01 lb
Dual-Range :	0-15 lb x 0.005 lb 15.01-30 lb x 0.01 lb

General 5956000

Power Source :	Compiled to 80Plus power saving for 100-120Vac Gold
Dimensions : mm/in	518/20.39 (W) X 284/11.18 (D) X 429/16.89 (H)
Net weight :	12.5 kg
Operation humidity :	15% to 85% RH Non-Condensation

Consoles

Operator Display and Customer Display :	8" TFT WVGA with Capacitive Touch (480 x 800) 8" TFT WVGA (480 x 800)
Keyboard :	18 x Keypads (For 8" Operator only)
Standard Interface :	Ethernet 10/100 Base T, 4 x USB 2.0, RJ11

Label Receipt:

Roll Diameter :	Max 95mm (3.74 in)
Print Width :	Max 60mm (2.36 in)
Paper Width :	Max 62mm (2.44 in)
Printing Speed :	Max 150 mm/sec (5.91 in)
Printing Resolution :	300 dpi

Weighing

Capacity :	30 lb x 0.01 lb/ 0.15 lb/ 0.005 lb
Single-Range :	0-30 lb x 0.01 lb
Dual-Range :	0-15 lb x 0.005 lb 15.01-30 lb x 0.01 lb