

AW-5600AT PC BASED WRAPPER



8055600

DIGI AW-5600AT is a high-performance automatic weigh-wrap-label system designed for operational comfort and environmental friendliness. Reduces work load with easy and simplified operation, and conserves film and label consumption to achieve lower cost and a smaller environmental footprint.

High Productivity

Increases productivity with high speed processing of up to 36 packages a minute. Automatically determines the optimum wrapping conditions by adjusting the degree of film stretching, depending on commodity size fed into the machine.

Economical & Ecological

Super-stretch technology makes the best use of film and helps reduce film usage, while linerless labels eliminate wasteful margins and help reduce label consumption. An energy conservation mode helps reduce power consumption while the machine is not operating.

Labeling Options: Twin Labeler, POP Labeler, Bottom Labeler, Linerless Labeler

AW-5600FX PC BASED WRAPPER



8055600FX

DIGI AW-5600FX is an integrated semi-automatic weigh-wrap label system featuring the enhanced Pick-Pack System.

Handles a Wide Range of Wrapping Needs

The FX is superb at wrapping a challenging array of products . Fragile trays, irregularly-shaped trays, and even items without trays like fruits and vegetables, are quickly and beautifully wrapped and labeled. The FX will drastically reduce the need for a cumbersome hand wrapping operation.

Small Foot Print

Only a small footprint of 31.5"-36.8" is needed for installation.

Wraps Faster

Processes 17 packs per minute (max.) This increases operation efficiency.

AW-5600CPR PC BASED WRAPPER



8055600CPR

DIGI AW-5600CPR is a fully integrated weigh-wrap label system designed for in-line operation. The CPR meets demanding output by increasing efficiency of in-line weighing and packaging operations.

High Productivity

In addition to maintaining a speed of 30 packs/ min., the combination of tray presser and enhanced heater conveyor ensures a tight film seal and an attractive finish for the packaged product.

Space-efficient Production Lines

The CPR's remarkably compact 7.86 ft² footprint (excluding conveyor) helps you design an inline weighing and wrapping operation with maximum space efficiency.

MORE INFO ON NEXT PAGE →

General 8055600

Externals	Resin and stainless steel construction
Power Source and power consumption :	208/240V; Single Phase; 20A; 50/60Hz; 2.7kVA 1.7kW Peak
Dimensions : mm/inches	410/55.5 (W) X 1535/60.4 (D) X 1465/57 (H)
Net weight :	Approx.400kg (Single Labeler Type)
Operation humidity :	90%RH (max.)

Labeling

Label type :	Thermal paper
Application :	Automatic label
Label size : mm/ in	Width: 40-80/1.6-3.1 Length: 28-105/1.1-4.1
Dot density:	12 dot/mm (300 dpi)

Wrapping

Package size : mm/ inches	Width:130-380/5.1-15 Height:10-130*/ 0.4-5.1 *150mm is standard and 130mm is a factory option
	Depth: 80-254/3.1-10 The maximum combination of the above dimensions is not available and available package size depends on the film width.
Wrapping speed :	Max. 36 packages/min.
# of film roll:	One Roll
Film width :	350-450mm
Film length :	Max. 1,500m

Weighing

	Multi Interval		Single Interval
Capacity	Max 6/15kg	Max 3/6kg	Max 30lb
Scale interval	e=2/5g	e=1/2g	e=0.01 lb

General 8055600FX

Externals	Resin and stainless steel construction
Power Source and power consumption :	208/220/230/240V; 1Ø/3Ø; 1.8kVA, 1.8kW 220-240V; 1Ø; 50/60Hz; 7.5A; 1.8kVA, 1.8kW
Dimensions : mm/inches	800/31.5 (W) X 935/36.8 (D) X 1428.5/56.24(H)
Net weight :	Approx.250kg (Single Labeler Type)
Operation humidity :	90%RH (max.) with no condensation

Labeling

Label type :	Die-cut label	Linerless label
Label width:	25-80mm/0.98-3.1 in	44-59mm/1.73-2.3 in
Label length :	20-150mm/0.79-5.9 in	20-500mm/0.79-19.7in
Dot density:	12 dot/mm (300 dpi)	

Wrapping

Package size : mm/ in	Width:80-350 / 3.1-13.8 Height:10-130 / 0.4-5.1
	Depth: 80-230 / 3.1-9.0 The maximum combination of the above dimensions is not available and available package size depends on the film width.
Wrapping speed :	Max. 17 packages/min.
# of film roll:	One Roll
Film width :	350-500mm
Film length :	Max. 1,500m

Weighing

	Multi Interval		Single Interval
Capacity	Max 6/15kg	Max 3/6kg	Max 30lb
Scale Interval	e=2/5g	e=1/2g	e=0.01 lb

General 8055600CPR

Externals	Resin and stainless steel construction
Power Source and power consumption :	208/240V; 3Ø; 50/60Hz; 2.1kVA 220-240V; 1Ø; 50/60Hz; 2.0kW
Dimensions : mm/in	1060/41.7 (W) X 1404/55.3 (D) X 1786/70.3 (H)
Net weight :	Approx.340kg (Single Labeler Type)
Operation humidity :	90%RH (max.) with no condensation

Labeling

Label type :	Die-cut label	Linerless label
Label width:	40-80mm/1.6-3.1 in	44-59mm/1.73-2.3 in
Label length :	28-105mm/1.1-4.1 in	28-105mm/1.1-4.1 in
Dot density:	12 dot/mm (300 dpi)	

Wrapping

Package size : mm/ in	Width:130-350 / 5.1-13.8 Height:10-150 / 0.4-5.9
	Depth: 80-230 / 3.1-9.0 The maximum combination of the above dimensions is not available and available package size depends on the film width.
Wrapping speed :	Max. 30 packages/min.
# of film roll:	One Roll
Film width :	350-500mm
Film length :	Max. 1,500m

Weighing

	Multi Interval		Single Interval
Capacity	Max 6/15kg	Max 3/6kg	Max 30lb
Scale Interval	e=2/5g	e=1/2g	e=0.01 lb

Product Strap Banding Machine

8052263 RGW-560 Banding Machine with Console, Thermal Transfer Printer, 12 packages/minute. 100-120 or 220-240V, 50/60hz

Impact Product Presentation

Flexible Design Printing

Secure Packaging



AW-5600CP Wrapper

8055600CP1 *AW-5600CP is the basic model of the 5600 series, providing an impressive 30 packages/minute throughput in a reduced-cost design. The compact form factor retains the full-spec 300 dpi high-res printer and extra-large full-color touch-screen display that are standard with the 5600 series. The newly developed rotational labeler arm allows fully automatic application of linerless labels. Variations include models with manual or automatic label application.*

High

Productivity

Economical & Ecological

Easy Clean Up, Every Time



Meat, Bakery Dept. 60mm x 95mm

DIGI SM90, DP90, SM25, SM70, SM720, SM5500



All Labels Sold Per Roll

3351345 60mm x 95mm blank white label, for SM90 scale, non-perforated, 450 labels per roll (24 rolls per case)

60mm x 43mm Labels

- 3351250 60mm x 43mm Blue/Red Stock Label For SM90 Scale - 1000 per roll
- 3351300 60mm x 43mm Blank White Labels 991/Roll For DPI20 Printer

Bakery, Meat Depts. 60mm x 80mm

DIGI 3600-series, AW-4600, SM25, SM70, DP90, SM90, SM720, SM5500



ALL LABELS SOLD PER ROLL

- 3357827 60mm x 80mm safe handling label with large core for IL3600 and AW3600 machines, out side wind, 3 rolls per case, 1800 labels per roll
- 3356080 60mm x 80mm blank white label for SM90 scale, 24 rolls per case, 550 labels per roll
- 3357830 60mm x 80mm Blank Scale Label For AW4600 Wrapper - 1800 Labels Per Roll
- 3356075 60mm x 80mm Safe Handling Labels For SM90 - 550 Per Roll 24 Rolls Per Case